

SARV RANG PRODUCT DATA SARV COAT 3622 ACRYLIC PUTTY COATINGS



DESCRIPTION

Sarv coat 3622 is a quick drying putty based on thermoplastic acrylic resin.

OUTSTANDING CHARACTERISTICS

- High adhesion to different paints and substrates
- Good mechanical properties.
- Excellent flexibility.

RECOMMENDED USE

Applicable for filling pores & smoothing the concrete and wood and carbon steel surfaces.

The consistency can be adjusted by thinner SVT- 36

SURFACE PREPARATION

The surface must be clean, dry and free from any contaminations such as grease, rust, salt and loose paint.

PHYSICAL DATA

Finish.....	Flat
Colour.....	Upon request
Volume Solids.....	60±2%
Specific Gravity.....	2.1±0.05 gr/cm ³
Flash Point.....	70°C
Touch dry.....	30 min .at 20°C
Hard dry.....	24 hrs.at 20°C
Shelflife	12 months at 20°C
Package.....	20 liter container

APPLICATION DETAILS

Application method.....	Knife
Application temperature.....	0-50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT-36
Pot life	N/A
Over coating	Min. 24 hrs. Max. Non limitation

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار