

SARV RANG PRODUCT DATA SARV COAT 6720  
ALKYD SEALER COATINGS



## DESCRIPTION

Sarv coat 6720 is air-drying alkyd sealer.

## OUTSTANDING CHARACTERISTICS

- Excellent penetration effect into the pores.
- Good bending effect on paint layers.

## RECOMMENDED USE

As a mist coat on metal and sealer coat on concrete surfaces to penetrate into the pores make porous surfaces smooth.

## SURFACE PREPARATION

Remove oil and grease, etc. with suitable detergent.

Remove salt and other contaminants by (high pressure) fresh water cleaning. Clean damaged area thoroughly by power tool cleaning to ST3 (minor areas)

Or by abrasive blasting to minimum Sa2, preferably to Sa2 ½ (for repair and maintenance)

Abrasive blasting to Sa 2½, SSPC-10 (for new steel)

## PHYSICAL DATA

|                           |                            |
|---------------------------|----------------------------|
| Finish.....               | semi gloss                 |
| Colour.....               | non pigmented              |
| Volume Solids.....        | 40±2%                      |
| Specific Gravity.....     | 1±0.05 gr/cm <sup>3</sup>  |
| Flash Point.....          | 30°C                       |
| Dry film thickness.....   | 25 microns                 |
| Touch dry.....            | 2 hrs at 20°C              |
| Hard dry.....             | 6 days                     |
| Theoretical coverage..... | 16.8 sqm/lit.<br>16 sqm/kg |
| Practical Coverage.....   | Depends on loss factor     |
| Shelf life .....          | 12 months at 25°C          |
| Package.....              | 20 liter container         |

## APPLICATION DETAILS

|                              |                           |
|------------------------------|---------------------------|
| Application method.....      | Air Spray, Brush, Roller  |
| Application temperature..... | 10-50°C                   |
| Thinner/Cleaner.....         | SVT-67                    |
| Pot life .....               | N/A                       |
| Recoat interval.....         | Min. 1 hrs.<br>Max 2 days |

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6  
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار