

SARV RANG PRODUCT DATA SARV COAT 2730 VINYL ANTI-FOULING COATINGS



DESCRIPTION

Sarv coat 2730 is a physically drying anti-fouling topcoat based on a vinyl copolymer resin with a high toxicity level.

OUTSTANDING CHARACTERISTICS

- High toxicity providing excellent anti-fouling property
- Excellent water resistance
- Excellent durability

RECOMMENDED USE

As a anti-fouling topcoat for vinyl system on exterior of immersed marine steel structures and ships.

SURFACE PREPARATION

The surface must be clean, dry and free from any contamination such as grease, rust, mill scale, salt and loose paint. Old painted surfaces must be cleaned with high pressure water guns.

PHYSICAL DATA

| | |
|---------------------------|--------------------------------------|
| Finish..... | Flat |
| Colour..... | Red |
| Volume Solids..... | 52±2% |
| Specific Gravity..... | 1.6 ±0.1 gr/cm ³ |
| Flash Point..... | 30°C |
| Recommended D.F.T..... | 30-50 microns |
| Theoretical coverage..... | 17.3-10.4 sqm/lit 10.8-6.5 sqm/kg |
| Touch dry..... | 30 min at 20°C |
| Hard dry..... | 180 min at 35 °C |
| Shelf life..... | 1 year |
| Package..... | 4 & 20 liter container |

APPLICATION DETAILS

| | |
|------------------------------|----------------------------------|
| Application method | Air/Airless spray, Brush, Roller |
| Application temperature..... | 10 - 40°C |
| Mixing ratio..... | single pack |
| Thinner/Cleaner..... | SVT-27 |
| Pot life | N/A |
| Recoat interval..... | Min 24 hrs Max 2 moths |

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار