

# SARV RANG PRODUCT DATA SARV COAT 2968 VINYL DECORATIVE COATINGS



## DESCRIPTION

Sarv coat 2968 is a versatile water base decorative paint based on PVA.

## OUTSTANDING CHARACTERISTICS

- Good colour retention
- Excellent processability
- Excellent recoatability
- Good washability

## RECOMMENDED USE

As a decorative coat on building walls and massonaries.

## SURFACE PREPARATION

The surface must be clean, dry and free from any contamination such as grease, rust, salt and loose paint.

## PHYSICAL DATA

Finish.....	Flat
Colour.....	Upon request
Volume Solids.....	35±2%
Specific Gravity.....	1.4 ±0.05 gr/m <sup>3</sup>
Recommended D.F.T.....	75 microns
Theoretical coverage.....	4.6 sqm/lit 3.3 sqm/kg
Touch dry.....	1-2 hrs at 20°C
Hard dry.....	2-3 dary at 20 °C
Practical Coverage.....	Depends on loss factor
Shelf life.....	1 year
Package.....	4 liter container

## APPLICATION DETAILS

Application method .....	Air spray, Brush, Roller
Application temperature.....	10 - 50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	water
Pot life .....	N/A
Recoat interval.....	Min 5 hrs Max none

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6  
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار