

SARV RANG PRODUCT DATA SARV COAT 3168
ACRYLIC TRAFFIC COATINGS



DESCRIPTION

Sarv coat 3168 is a quick drying based on thermoplastic acrylic resin.

OUTSTANDING CHARACTERISTICS

- High adhesion to concrete and asphalt
- Excellent abrasion resistance
- Excellent water and alkali resistance.

RECOMMENDED USE

Suitable for use on concrete and asphalt, specially for road marking.

SURFACE PREPARATION

The surface must be clean, dry and free from any contamination such as dust, grease, oil, salt and loose paint.

PHYSICAL DATA

Finish.....	Flat
Colour.....	white, yellow, black
Volume Solids.....	49±2%
Specific Gravity.....	1.37±0.05 gr/cm ³
Flash point.....	33 °C
Recommended D.F.T.....	200-400 microns
Theoretical coverage.....	2.4-1.2 sqm/lit. 1.7-0.85 sqm/kg
Practical Coverage.....	Depends on loss factor
Dry through.....	30 min
Shelf life	12 months
Package.....	20 liter container

APPLICATION DETAILS

Application method.....	Automatic spray or hand application
Application temperature.....	0-50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT-31
Pot life	N/A
Recoat interval.....	No limitation

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار