

SARV RANG PRODUCT DATA SARV COAT 3930 ACRYLIC EMULSION TOPCOAT COATINGS



DESCRIPTION

Sarv coat 3930 is a waterborne alkali resistant, acrylic topcoat in ant carbonation system. The product is water- repellent, but allows water vapour from the substrate pass through the film.

OUTSTANDING CHARACTERISTICS

- Excellent water resistance
- Good appearance
- Good flexibility
- Good weather resistance
- Good washablity
- Good U.V resistance

RECOMMENDED USE

As a topcoat applicable in paint system in interior and exterior of buildings.

SURFACE PREPARATION

The surface of primer must be clean, dry and free from any contamination such as grease, salt and loose paints.

PHYSICAL DATA

Finish.....	Flat
Colour.....	limited
Volume Solids.....	43±2%
Specific Gravity.....	1.45±0.05 gr/cm ³
Recommended D.F.T.....	100-150 microns
	Per two coats
Theoretical coverage.....	4.3-2.86 sqm/lit.
	2.96-1.97 sqm/kg
Practical Coverage.....	Depends on loss factor
Touch dry.....	30 min.at 20°c
Hard dry.....	5 days at 20°c
Shelflife	12 months
Package.....	20 liter container

APPLICATION DETAILS

Application method.....	Air spray, Brush, Roller
Application temperature.....	5-40°c
Mixing ratio.....	single pack
Thinner/Cleaner.....	water
Pot life	N/A
Recoat interval.....	Min. 6 hrs.
	Max. None

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
 کد پستی: 1473913774
 تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187
 فکس: 44037529 ایمیل: sarvrang.co@gmail.com
 آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار