

SARV RANG PRODUCT DATA SARV COAT 3931
ACRYLIC EMULSION PRIMER COATINGS



DESCRIPTION

Sarv coat 3931 is a physically drying primer based on acrylic emulsion resin.

OUTSTANDING CHARACTERISTICS

- Excellent penetrating effect.

Promotes adhesion between coating layers & substrate.

RECOMMENDED USE

As a primer on concrete & masonry interior & exterior of wall and buildings.

SURFACE PREPARATION

The surface must be clean, dry & free from any contamination such as grease, salt and loose paint.

PHYSICAL DATA

Finish.....	Flat
Colour.....	limited
Volume Solids.....	45±2%
Specific Gravity.....	1.45±0.05 gr/cm ³
Recommended D.F.T.....	30-50 microns
Theoretical coverage.....	13.3-8 sqm/lit 9.3-5.6 sqm/kg
Practical Coverage.....	Depends on loss factor
Touch dry.....	30 min .at 20°c
Hard dry.....	3 days at 20°c
Shelf life	12 months
Package.....	20 liter container

APPLICATION DETAILS

Application method.....	air spray, Brush, Roller
Application temperature.....	10-40°c
Mixing ratio.....	single pack
Thinner/Cleaner.....	water
Pot life	N/A
Recoat interval	Min. 6 hrs. Max. None

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
 کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار