

SARV RANG PRODUCT DATA SARV COAT 6722

ALKYD MEDIUM INTERMEDIATE COATINGS



DESCRIPTION

Sarv coat 6722 is a versatile intermediate/finish coat based on long oil alkyd resin.

OUTSTANDING CHARACTERISTICS

- Excellent sprayability
- Good UV resistance
- Good resistance in mildly to moderate corrosive environments

RECOMMENDED USE

As an intermediate/finish coat on exterior and interior of steel structures previously primed with alkyd primers.

SURFACE PREPARATION

The surface must be clean, dry and free from any contamination such as grease, rust, salt and loose paint.

Old primed surfaces should be roughened.

PHYSICAL DATA

Finish.....	Flat
Colour.....	Grey
Volume Solids.....	54±2%
Specific Gravity.....	1.45±0.05 gr/cm ³
Flash Point.....	38°C
Recommended D.F.T.....	40-60 microns
Theoretical coverage.....	13.5-9 sqm/lit. 9.3-6.2 sqm/kg
Touch dry.....	18 min at 20°C 2 hrs at 35°C
Hard dry.....	1 week at 20°C
Thermal Resistance.....	continuous 120°C
Practical Coverage.....	Depends on loss factor
Shelf life	1 year at 25°C
Package.....	4 or 20 liter container

APPLICATION DETAILS

Application method.....	Air /Airless spray, Brush, Roller
Nozzle orifice.....	.019"- .021"
Nozzle pressure.....	150 bar/ 2200 Psi
Application temperature.....	10-50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT 67
Pot life	N/A
Recoat interval.....	Min. 24 hrs. Max 1 months

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: حاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار