

SARV RANG PRODUCT DATA SARV COAT 6724 ALKYD ZINC PHOSPHATE COATINGS



DESCRIPTION

Sarv coat 6724 is a preventing, zinc phosphate pigmented Primer based on long oil alkyd resin.

OUTSTANDING CHARACTERISTICS

- Excellent Rust preventing
- Excellent sprayability
- Excellent flexibility
- High Resistance in corrosive and humid industrial environments

RECOMMENDED USE

For use on structural steel e.g building, ware houses, bridges, as part of a suitable alkyd based paint system.

SURFACE PREPARATION

Remove oil and grease, etc with suitable detergent

Remove salt and other contaminants by (high pressure) fresh water cleaning.

Abrasive blasting to minimum Sa 2 alternatively power tool cleaning to ST3.

PHYSICAL DATA

Finish.....	Flat
Colour.....	Upon request
Volume Solids.....	53±2%
Specific Gravity.....	1.3±0.05 gr/cm ³
Flash Point.....	33°C
Recommended D.F.T.....	40-60 microns
Theoretical coverage.....	12-8 sqm/lit. 8.57-5.71 sqm/kg
Practical Coverage.....	Depends on loss factor
Touch dry.....	180 min at 20°C
Deep dry.....	1 week at 20°C
Thermal Resistance.....	120°C
Shelf life	12 months at 25°C
Package.....	20 liter container

APPLICATION DETAILS

Application method.....	Air /Airless spray, Brush, Roller
Nozzle orifice.....	.018" - .021"
Nozzle pressure.....	150 bar/ 2200 Psi
Application temperature.....	10-50°c
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT-67
Pot life	N/A
Recoat interval.....	Min. 24 hrs. Max 1 months

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار