

SARV RANG PRODUCT DATA SARV COAT 6726 ALKYD RED OXID PRIMER COATINGS



DESCRIPTION

Sarv coat 6726 is a general purpose red oxide primer based on long oil alkyd resin.

OUTSTANDING CHARACTERISTICS

- Rust preventing
- Excellent sprayability
- Excellent flexibility
- Good Resistance in mildly to moderate corrosive environment

RECOMMENDED USE

For use on structural steel to be topcoated with oil based finish coats.

SURFACE PREPARATION

Remove oil and grease, etc with suitable detergent

Remove salt and other contaminants by (high pressure) fresh water cleaning.

A brasive blasting to minimum Sa 2 alternatively power tool cleaning to ST3.

PHYSICAL DATA

Finish.....	Flat
Colour.....	Red-Brown
Volume Solids.....	48±2%
Specific Gravity.....	1.5±0.05 gr/cm ³
Flash Point.....	38°C
Recommended D.F.T.....	40-60 microns
Theoretical coverage.....	12-8 sqm/lit. 8-5.3 sqm/kg
Practical Coverage.....	Depends on loss factor
Touch dry.....	3 hrs at 20°C
Hard dry.....	1 week at 20°C
Shelf life	12 months at 25°C
Thermal Resistance.....	100°C
Package.....	20 liter container

APPLICATION DETAILS

Application method.....	Air /Airless spray, Brush, Roller
Nozzle orifice.....	.018" - .021"
Nozzle pressure.....	150 bar/ 2200 Psi
Application temperature.....	10-50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT 67
Pot life	N/A
Recoat interval.....	Min. 24 hrs. Max 1 months

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار