

SARV RANG PRODUCT DATA SARV COAT 6868 ALKYD HIGH CLOSSTOPCOAT COATINGS



DESCRIPTION

Sarv coat 6868 is a general purpose glossy topcoat based on medium oil alkyd resin.

OUTSTANDING CHARACTERISTICS

- High gloss and colour retention
- Fast drying
- Excellent sprayability
- Good oil resistance
- Good resistance in mildly to moderate corrosive environments.

RECOMMENDED USE

As a high gloss finish coat over alkyd primed industrial steel surfaces such as industrial engines, automobiles, wagons, containers etc...

SURFACE PREPARATION

The surface must be undamaged, clean, dry and free from any contamination such as grease, rust salt and loose paint.

PHYSICAL DATA

Finish.....	Gloss
Colour.....	Upon request
Volume Solids.....	50±2%
Specific Gravity.....	1.15±0.1 gr/cm ³
Viscosity(Ford cup No.4).....	180±10 sec
Flash Point.....	30°C
Recommended D.F.T.....	40-60 microns
Touch dry.....	1.5 hrs at 20°C
Hard dry.....	16 hrs at 20°C
Theoretical coverage.....	12.5-8.3 sqm/lit. 10.8-7.2 sqm/kg
Practical Coverage.....	Depends on loss factor
Thermal Resistance.....	continuous 120°C Noncontinuous 130°C
Shelf life	12 months at 20°C
Package.....	20 liter container

APPLICATION DETAILS

Application method.....	Air /Airless spray, Brush, Roller
Application temperature.....	5-50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT-68
Pot life	N/A
Recoat interval.....	Min. 16 hrs. Max indefinite

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار