

SARV RANG PRODUCT DATA SARV COAT 7168
CHLORINATED RUBBER SWIMMING POOL COATINGS



DESCRIPTION

Sarv coat 7168 is a physically drying, modified chlorinated rubber based coating.

OUTSTANDING CHARACTERISTICS

- Excellent water resistance
- Fast drying
- Good penetration.
- Good appearance.

RECOMMENDED USE

As a water resistant paint in swimming pools or cementitious water reservoirs.

SURFACE PREPARATION

The surface must be clean and dry. Remove oil, grease, salt and any other contamination with suitable solvent and by high pressure fresh water.

PHYSICAL DATA

Finish.....	Flat
Colour.....	blue and or request
Volume Solids.....	46±2%
Specific Gravity.....	1.25±0.05 gr/cm ³
Flash Point.....	24°C
Recommended D.F.T.....	27-100 microns
Theoretical coverage.....	6.1-4.6 sqm/lit.
.....	4.93-3.70 sqm/kg
Practical Coverage.....	Depends on loss factor
Touch dry.....	8 hrs at 20°C
Shelf life	1 year at 25°C
Package.....	20 liter container

APPLICATION DETAILS

Application method	Air/Airless spray, Brush, Roller.
Nozzle orifice.....	.021"-.023"
Nozzle pressure.....	150 bar/2200 Psi
Application temperature.....	10-50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT-71
Pot life	N/A
Recoat interval.....	Min 6 hrs at 20°C
	Max none (see remarks overleaf)

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
 کد پستی: 1473913774

تلفن: 44037532 - 44037534 - 44486491 - 44043081 - 44045187

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار