

SARV RANG PRODUCT DATA SARV COAT 7737 CHLORINATED RUBBER TRAFFIC PAINT



DESCRIPTION

Sarv coat 7737 is a physically drying, modified chlorinated rubber based traffic paint.

OUTSTANDING CHARACTERISTICS

- Excellent abrasion resistance.
- Excellent water and alkali resistance
- Good appearance.
- High adhesion to concrete and asphalt

RECOMMENDED USE

Suitable for use on concrete and asphalt , specially for road marking.

SURFACE PREPARATION

The surface must be clean, dry and free of grease, mill- scale, rust and dirt.

PHYSICAL DATA

Finish.....	Flat
Colour.....	Upon request
Volume Solids.....	40±2%
Specific Gravity.....	1.35±0.05 gr/cm ³
Flash Point.....	24°C
Recommended D.F.T.....	100-150 microns
Theoretical coverage.....	4-2.7 sqm/lit.
.....	2.96-2 sqm/kg
Practical Coverage.....	Depends on loss factor
Touch dry.....	60 min at 20°C
Hard dry.....	24 hours at 20°C
Thermal Resistance.....	Continuous 60° Non-continuous 65 °C
Shelf life	12 months at 25°C
Package.....	20 liter container

APPLICATION DETAILS

Application method	Automatic or hand application
Application temperature.....	10-50°C
Mixing ratio.....	single pack
Thinner/Cleaner.....	SVT-77
Pot life	N/A
Recoat interval.....	No limitation

دفتر مرکزی: تهران، آیت الله کاشانی، ابتدای جنت آباد جنوبی، نیش کوچه پاستور، ساختمان سهیل، واحد 5 و 6
کد پستی: 1473913774

تلفن: 44037529 - 44043081 - 44486491 - 44037534 - 44037532

فکس: 44037529 ایمیل: sarvrang.co@gmail.com

آدرس کارخانه: جاده خاوران، کیلومتر 9 شریف آباد، بعد از شهرک صنعتی عباس آباد، انتهای بلوار نگار